

PC80X, 110X & 150 Premium Choice

(Ceiling Mounted Ventilation Fans)

JencoFan

6393 Powers Avenue
Jacksonville, Florida 32217-2298
P: 904.731.4711 / F: 904.737.8322
www.Jencofan.com

Soler&Palau
Ventilation Group



Performance

Model	CFM	Static Pressure (in W.G.)	Energy Efficiency (CFM/Watts)*	Watts	Power (V/Hz)	Sones	Amps	ENERGY STAR
PC80X	80/60	0.1/0.25	3.0	32	120/60	0.3	.27	Yes
PC110X	110/93	0.1/0.25	3.2	36	120/60	0.6	.30	Yes
PC150	150/110	0.1/0.25	3.8	41	120/60	1.1	.34	Yes

* Energy Star qualified data based on tested air flow and power consumption.

Dimensions

Model	Duct Dia.	Grille Size (Sq. in inches)	Cabinet Size (in Inches)			Unit Wgt. (lbs)
			W	D	H	
PC80X	4 or 6"	13 x 14	11-3/8	10-1/2	7-5/8	8
PC110X	4 or 6"	13 x 14	11-3/8	10-1/2	7-5/8	9
PC150	6"	13 x 14	11-3/8	10-1/2	7-5/8	9

Typical Specifications:

Ventilating fan shall be JencoFan PC80X, PC110X or PC150 mounted in the ceiling. The fan shall have a 5 year limited warranty. The fan shall be HVI Certified at 0.1 inch water gauge for CFM performance above. The motor shall be ETL and cETL Listed with impedance protection plus additional thermal protection. PC80X, 110X & 150 shall be Energy Star Qualified.

For more information contact us at www.Jencofan.com for additional submittal drawings.

JencoFan will not be responsible for fabrication changes or errors resulting from customer use of a non-current submittal drawing.