



PCXP AC Motor Models



PCD DC Motor Models



PCV Value Series Models



PCLP / PCLPXP Low Profile Models

BATHROOM FAN SIZING

Based on the Home Ventilating Institute (HVI) guidelines

5′

FAN SIZING FOR BATHROOMS UNDER 100 SQUARE

FEET

The standard rule for bathrooms 100 square feet or smaller is one CFM per square foot of the bathroom. To find the square footage, multiply the length of the bathroom by the width.

9

45 sq.ft.

The minimum recommendation is a fan rated at least 45 CFM.

Ventilation for baths over 100 square feet is calculated based on the fixtures in the bathroom (see table below). Add the CFM of all fixtures within the bathroom for the required fan CFM. Enclosed toilet rooms must have an operable window or a fan for ventilation.

CFM REQUIRED PER FIXTURE

Toilet	50 CFM
Shower	50 CFM
Bath Tub	50 CFM
Jetted Tub	100 CFM

EXAMPLE

1 Toilet	50 CFM	
1 Jetted Tub	100 CFM	
Required CFM	150 CFM	



SOLUTION

- 1. Install a 100 CFM fan over the tub, 50 CFM fan in the shower and above the toliet. This method will provide ventilation where and when it's needed.
- 2. Install one 150 CFM fan. The air will be pulled through the entire room and exhausted at a central location.

For more information on bath fan sizing and ventilation, visit www.hvi.org.

IMPROVE IAQ WITH THE PREMIUM CHOICE SERIES

Americans spend
of their time
INDOORS.







As buildings are being built with higher quality construction methods, balanced ventilation methods are more important than ever. An unbalanced home results in poor Indoor Air Quality (IAQ), causing inadequate conditions for your home and the inhabitants. As codes change, it is important for you to understand why Indoor Air Quality is so important and the options available to you from S&P USA.

Locate the best fan for your project to the right.

SERIES	MODEL	CFM	SONES +	PAGE
	PC50XP	50	0.4	8
PCXP	PC80XP	80	0.4	8
AC Motor Models	PC 110XP	110	0.3	8
	PC150XP	150	0.5	8
PCD	PCD80XH	80	1.5	10
DC Motor	PCD 110XP	80/110/140	0.3/0.3/0.3	10
Models	PCLPD100XHP	100/80/50	1.2/1.0/0.6	12
PCV	PCV50	50	2.5	14
Value Series Models	PCV80	80	1.5	14
	PCLP80	80	1.2	15
PCLP	PCLP100	100	2	15
Low Profile	PCLP80XP	80	0.7	16
Models	PCLP100XP	100	1.5	16
	PCLPD100XHP	100/80/50	1.2/1.0/0.6	12

PREMIUM CHOICE DIFFERENCE



LONG LIFE



BEST IN CLASS WARRANTY



STRESS-FREE INSTALLATION



PLUG-&-PLAY DESIGN



ENERGY EFFICIENT

PLUG-&-PLAY MODULES + GRILLES


S&P's unique Plug-&-Play options make your CHOICE easy. Whether you're looking for a Speed Control, Humidity Sensor, Motion/Humidity Sensor or VOC Sensor, there is a control that connects to the receptacle and easily mounts into the pre-drilled holes inside the fan housing.

There is a receptacle for your grille CHOICE.

Need a lighted fan? Choose the fluorescent or LED Lighted Grille Kits. Need a motion sensing fan?

Choose the Motion Sensing Grille Kit. Either grille easily plugs into the grille receptacle to give you the fan of your CHOICE!

PC Fan models include receptacles based on compatibility. Learn more in our Accessories section.



MODULES + GRILLES

- Humidity Sensor
- Volatile Organic Compound + Humidity Sensor
- Speed Control
- Motion + Humidity Sensor
- Grille Kit
- CFL Lighted Motion Grille
- LED Lighted Grille
- Lighted Motion Grille



^{*}The receptacle for the PCIAQS is field installed.

UNDERSTANDING PLUG-&-PLAY

PICK YOUR FAN

Pick a base fan from one of our Premium CHOICE Series models.

EXAMPLE: PC110XP AC Model



PICK YOUR MODULE OR GRILLE

Choose a compatible Module or Grille Kit for your custom need

EXAMPLE: PCLMHKP Lighted Motion and --Humidity Sensor Kit for PCXP Series



ORDER YOUR CUSTOM FAN

Order your Base Fan + Module/Grille to receive your full custom fan.

EXAMPLE: PC110XP + PCLMHKP



PCXP - AC MOTOR MODELS

















FEATURES

- Extremely quiet operation 0.3 to 0.5 sones
- Redesigned blower for increased efficiency and lower sound
- Seamless Plug-&-Play integration
- Select models available as Contractor Packs (packs of 4)

MODEL	CFM	sones †
PC50XP	50	0.4
PC80XP	90	0.4
PC 110XP	120	0.3
PC150XP	150	0.5

MODULES + GRILLES

HUMIDITY SENSOR PCHSP



SPEED CONTROL PCSCP



VOLATILE ORGANIC COMPOUND AND HUMIDITY SENSOR PCIAQSP



METAL GRILLE **PCMGP**



CFL LIGHTED GRILLE
PCLKP



LIGHTED MOTION
AND HUMIDITY
GRILLE KIT
PCLMHKP



RADIATION DAMPER
PCRD



MOTION AND HUMIDITY
GRILLE KIT
PCMHKP



LED LIGHTED GRILLE **PCLEDKP**



LED LIGHTED GRILLE
PCVLEDKP
for PC50XP



RADIATION DAMPER PCVRD



^{*} UL certified includes 230V ONLY

⁺ Sones shown are at .1" of Static Pressure

PCXP - AC MOTOR MODELS

Fan Model	Accessory	Compatible with:
	PCSCP	
	PCHSP	PCVRD, PCVLEDKP, PCVLEDKRDP
PC50XP	PCVRD	
	PCVLEDKP	PCSCP, PCHSP
	PCVLEDKRDP	
	PCSCP	
	PCHSP	PCLKP, PCLEDKP, PCMGP, PCRD, PCLKRDP, PCLEDKRDP, PCMGKRDP
	PCIAQSP	·
	PCLKP	
	PCLEDKP	PCSCP, PCHSP, PCIAQSP
	PCMGP	
PC80XP, PC110XP, PC150XP, PCHP, PC80XFP, PC110XFP	РСМНКР	
,	PCLMHKP	NA NA
	PCLKRDP	
	PCLEDKRDP	
	PCMGKRDP	
	PCMHKRDP	NA.
	PCLMHKRDP	NA NA

WHAT IS A CONTRACTOR PACK?

Contractor Packs are broken into two packages: Housing (set of 4) and Motors + Grilles (set of 4). This allows installation flexibility for large scale projects that need to be completed in phases.

AVAILABLE ON SELECT MODELS



PCD - DC MOTOR MODELS







- Extremely quiet operation 0.3 to 1.5 sones
- Brushless DC motor for long life
- High/Low speed delay timer
- Built in control module with motion, humidity, speed control, and delay timer (options vary per model)
- Motion grille(purchased separately) is required for motion sensing capability

	MODEL	CFM	sones †
	PCD80XHP	80	0.5
	PCD 110XP	110	0.3
_	PCLPD 100XHP	80	1.0













MODULES + GRILLES

FOR PCD80XHP

LED LIGHTED RADIATION GRILLE **PCVLEDKDP**



LED LIGHTED GRILLE **PCVLEDKP**



RADIATION DAMPER **PCVRD**



FOR PCD110XP

CFL LIGHTED GRILLE PCLKP



LED LIGHTED GRILLE **PCLEDKP**



METAL GRILLE **PCMGP**



MOTION GRILLE **PCMRGP**



LIGHTED MOTION AND HUMIDITY **GRILLE KIT**

PCDLMGP



FOR PCLPD100XHP

LED LIGHTED GRILLE
PCLPLEDK



LED LIGHTED GRILLE & RADIATION DAMPER KIT PCLPLEDKRD



4" OVAL TO 3" ROUND REDUCER PCLPR4-3



Model	Accessory	Compatible with:
	PCVLEDKP	
PCD80XHP	PCVLEDKRDP	NA
	PCVRD	
	PCLEDKP	
	PCLKP	
	PCMGP	
	PCDLMGP	
PCD 110XP	PCMRGP	NA
PCDITOXP	PCMRGRDP	INA INA
	PCLKRDP	
	PCLEDKRDP	
	PCMGKRDP	
	PCDLMGRDP	
	PCLPLEDK	
PCLPD 100XHP	PCLPLEDKRD	PCLPR4-3
	PCLPR4-3	



AUTOFLO™ FROM S&P USA

Autoflo[™] is an innovative technology that automatically adjusts the fan speed based on the actual Static Pressure in the duct system ensuring a specified amount of airflow. Available on PCD 80XHP and PCD 110XP.

Premium (hoice Series **Ventilation Fans**

PCLPD 100XHP

PCLPD 100XHP LOW PROFILE CEILING OR WALL MOUNTED EXHAUST FAN WITH DC MOTOR

S&P's Premium Choice Series Bathroom/Exhaust Fan model PCLPD100XHP is built for today's demanding requirements featuring seamless Plug-&-Play integration and a redesigned blower for a quiet, energy efficient performance. The PCLPD100XHP also features an ultra-low profile that allows easy installation into a wall, eliminating the need for a radiation damper to meet fire-resistance requirements in building code.

KEY FEATURES

- Ultra-Low Profile Design to fit in the smallest wall cavities
- Ultra-Quiet Operation of 1.2 sones
- DC Motor for high efficiency with auto-flow technology
- · Built-in Humidity Sensing and Continuous low speed capability
















PCLPD100XHP
Low Profile Ceiling
or Wall Mounted
Exhaust fan
with DC Motor

Model	Accessory	Compatible Wi
PCLPD100XHP ow Profile Ceiling	PCLPLEDK LED Lighted Grille Kit	·
r Wall Mounted Exhaust fan with DC Motor	PCLPLEDKRD LED Lighted Grille Kit & Radiation Damper	PCLPR4-3 Round Recuce





Radiation Damper

PCLPR4-3



Autoflo is an innovative technology that automatically adjusts the fan speed based on the actual Static Pressure in the duct system ensuring a specified amount of airflow.















PCV-VALUE MODELS





FEATURES

- Quiet operation 1.5 to 2.5 sones
- 4" duct connector with built-in backdraft
- Available as Contractor Packs (packs of 4)

MODEL	CFM	sones †
PCV50	50	2.5
PCV80	80	1.5









MODULES + GRILLES

HUMIDITY SENSOR SPEED CONTROL **PCHS**









LED LIGHTED GRILLE **PCVLEDK**







Model	Accessory	Compatible with:	
	PCHS	PCVRD, PCVLEDK	
	PCVRD	PCHS	
PCV50, PCV50H, PCV50F	PCVLK	N/A	
	PCVLEDK	PCHS	
	PCVLEDKRD	PCHS	
	PCSC	DCVDD DCV4FDV DCV4FDVDD	
	PCHS	PCVRD, PCVLEDK, PCVLEDKRD	
DCV00 DCV0011 DCV005	PCVRD	PCSC, PCHS	
PCV80, PCV80H, PCV80F	PCVLK	N/A	
	PCVLEDK	PCSC, PCHS	
	PCVLEDKRD	PCSC, PCHS	

PCLP-LOW PROFILE MODELS





- Low profile housing design
- Suitable for sidewall mounting
- Quiet operation 1.2 to 2.0 sones
- Available as Contractor Packs (Pack of 4)
- No ceiling radiation damper is required when wall mounted, saving time and money

MODEL	CFM	SONES †
PCLP80	80	1.2
PCLP100	100	2









OPTIONAL ACCESSORY

MODULES + GRILLES

PCLP 4" OVAL TO 3" **ROUND REDUCER**

PCLPR4-3



HUMIDITY SENSOR PCLPHS



PCLPSC



PCLPLEDK



SPEED CONTROL LED LIGHTED GRILLE RADIATION DAMPER **PCLPRD**



Model	Accessory	Compatible with:
PCLP80, PCLP100, PCLPH, PCLP100F	PCLPLEDK	
	PCLPRD/PCRD	PCLPSC, PCLPHS
	PCLPLEDKRD	
	PCLPSC	PCLPLEDKRD, PCLPLEDK
	PCLPHS	
	PCLPR4-3	Everything above

PCLPXP-LOW PROFILE MODELS





- Ultra-Low Profile Design to fit in the smallest wall
- Ultra-Quiet operation of .7 to 1.5 sones
- Available as Contractor Packs (Pack of 4)
- No ceiling radiation damper is required when wall mounted, saving time and money
- One SKU can be kept on hand for both wall and ceiling mounted applications to consolidate warehouse space.

MODEL	CFM	sones †
PCLP80XP	80	0.7
PCLP100XP	100	1.5







OPTIONAL ACCESSORY

MODULES + GRILLES

PCLP 4" OVAL TO 3"

ROUND REDUCER

PCLPR4-3





HUMIDITY SENSOR



PCLPSCP



PCLPLEDK

SPEED CONTROL LED LIGHTED GRILLE





Model	Accessory	Compatible with:
PCLP80XP, PCLP100XP, PCLPHXP, PCLP80XPF, PCLP100XPF	PCLPSCP	PCLPLEDK, PCLPRD/PCRD, PCLPLEDKRD
	PCLPHSP	
	PCLPLEDK	
	PCLPRD/PCRD	PCLPSCP, PCLPHSP
	PCLPLEDKRD	
	PCLPR4-3	Everything above

^{*}Values shown are at .1" of static pressure

GRILLES



METAL GRILLE -

PCMG/PCMGP

Ideal for commercial applications



Motion and Humidity Sensing Grille Kit -

PCMHKP

- Automatically turns on fan when motion or humidity is sensed
- Adjustable time delay shut-off from 5 to 60
- Speed Controllable low speed if enabled



Lighted Motion and Humidity Sensing Grille Kit -

PCLMHKP

- 13 watt GU24 bulb and 4 watt night light bulb
- Automatically turns on fan when motion and/or humidity is sensed
- Adjustable time delay shut-off from 5 to 60 minutes
- Speed Controllable low speed if enabled



CFL Lighted Grille Kit -

PCLK/PCLKP

13 watt GU24 bulb and 4 watt light bulb



LED Lighted Grille Kit-

PCLEDKP/PCLPLEDK

- 11 watt LED light
- 4100K/1100 lumens
- 2 watt LED night light setting 200 lumens



CFL Lighted Grille Kit for PC Value-**PCVLK**

- 13 watt GU24 bulb
- 2700K/900 lumens
- Simple plug-in receptacle in fan housing



LED Lighted Grille Kit for PC Value -

PCVLEDK/ PCVLEDKP

- 13 watt LED light
- 4100K/1100 lumens
- 2 watt LED night light setting 200 lumens
- Can be installed with new or pre-installed fan



LED Lighted Grille Kit-

PCLPLEDK

- 13 watt LED light
- 4100K/1100 lumens
- Simple plug-in receptacle in fan housing
- Can be installed with new or pre-installed fan

PLUG-&-PLAY MODULES



PCHS

PCHSP



PCLPHS

HUMIDITY SENSOR

- Detects rapid rise in humidity
- Auto-shut off timer
- Accessible sensitivity adjustment
- Meets Title 24 bathroom fan requirement





PCSC

PCSCP



PCLPSC SPEED CONTROL

- Provides seamless two speed operation without additional wiring at the wall
- Accessible speed adjustment
- High speed override
- Allows for adjustable continuous speed to meet ASHRAE 62.2



PCIAQSP

VOLATILE ORGANIC COMPOUND (VOC) AND HUMIDITY SENSOR

- Detects VOCs and/or rapid rise in humidity at the ceiling
- Speed control to run fan continuously
- Meets Calirfonia Title 24 bathroom fan requirement (CALGreen)

WALL CONTROLS OPTIONS



3-SWITCH CONTROL

PC3S

Three Rocker Combination Switch with ground screw terminals and push-in wiring

> **ELECTRONIC PUSH BUTTON TIMER**

> > EPBT-60

10-20-30-60 minute timer

Activate by pushing the button



FAN/LIGHT DELAY **TIMER SWITCH** FLTD-60

- Saves energy by automatically turning exhaust fan off
- One Switch controls fan and light
- Digital Timing circuit
- Fits single switch outlet box



ROTARY SPRING WOUND TIMER SRT-30

- Hold feature enables user to override the automatic shut-off function
- Press-on knob design ensures quick and easy installation
- CFL Compatible



ASHRAE 62.2 BATH FAN VENTILATION CONTROL FT-622

- Programmable DELAY and VENTI-LATION settings
- Works with ALL incandescent, CFL, fluorescent and LED lights up to
- Earn LEED and ENERGY STAR points for enhanced exhaust ventilation



PROGRAMMABLE FAN TIMER 24 HOURS / 7 DAYS FT247

- Hold feature enables user to override the automatic shut-off function
- Press-on knob design ensures quick and easy installation
- CFL Compatible

RADIATION DAMPER KITS

GENERAL FEATURES

- 3-hour rating ceiling radiation dampers
- · Ceramic fiber with fiberglass cover fire blanket
- Roll-formed frame 22 g. galvanized steel





CFL LIGHTED GRILLE AND RADIATION DAMPER KIT PCLKRDP



LED LIGHTED GRILLE AND RADIATION

DAMPER KIT

PCLEDKRD/PCLEDKRDP



MOTION AND HUMIDITY SENSING
GRILLE AND RADIATION DAMPER KIT
PCMHKRDP



LIGHTED MOTION AND HUMIDITY
SENSING GRILLE AND RADIATION
DAMPER KIT
PCLMHKRDP



METAL GRILLE AND RADIATION
DAMPER KIT
PCMGKRD/PCMGKRDP



LED LIGHT KIT FOR PREMIUM CHOICE
VALUE SERIES AND RADIATION DAMPER
KIT
PCVLEDKRD/PCVLEDKRDP



LED LIGHT KIT FOR PREMIUM CHOICE LOW PROFILE SERIES AND RADIATION DAMPER KIT PCLPLEDKRD



MOTION GRILLE AND RADIATION DAMPER KIT **PCMRGRDP**



LIGHTED MOTION AND HUMIDITY
SENSING GRILLE AND RADIATION
DAMPER KIT
PCDLMGRDP







S&P USA Ventilation Systems, LLC

6393 Powers Avenue
Jacksonville, FL 32217
T. 904-731-4711 • F. 904-737-8322
www.solerpalau-usa.com

S&P Canada Ventilation Products, Inc

6710 Maritz Drive Unit #7 Mississauga, ON L5W 0A1 - Canada T. 416-744-1217 • F. 416-744-0887 www.solerpalaucanada.com

