MODEL GED/GSD DIRECT DRIVE SIDEWALL PROPELLER FAN WITH INTEGRAL OSHA GUARD



Jacksonville, Florida 32217-2298 P: 904.731.4711 / F: 904.737.8322 www.Jencofan.com




STANDARD CONSTRUCTION FEATURES


- · Galvanized steel G90 panel assembly.
- Statically and dynamically balanced aluminum blades.
- Integral OSHA approved motor side guard.
- One piece spun venturi for maximum efficiency.
- Pre-punched mounting holes for easy installation.
- Unit suitable for all-angle construction.
- cULus Listed Standard 705 (optional)



Standard 705 (optional)



REAR VIEW



GED/GSD		Avg. Ship					
Size	Α	В	С	D	E*	F*	Wt. (lbs.)
10	16	10-1/2	1	2	11	9	30
12	16	12-1/2	1	2	14	12	30
14	20	14-1/2	1	2	14	12	34
16	20	16-1/2	1	2	14	12	37
18	24	18-1/2	1	2	15	13	45
20	24	20-1/2	1	2	15	13	50

- A. Outside dimension of square panel.
- B. Diameter of venturi.
- C. Width of flange, 1" for all models.
- D. Depth of venturi, 2" for all models.
- E. Depth of fan (exhaust).
- F. Depth of fan (supply).
- * Varies with motor selection.

FAN SPECIFICATIONS								MOTOR SPECIFICATIONS					
Line	Qty.	Model No.	Tag	CFM	SP	Fan RPM	ВНР	Sones	HP	Volts	Phase	Hertz	Encl
1													
2													
3													
4													
5													

ACCESSORY ITEMS	1	2	3	4	5	ACCESSORY ITEMS	1	2	3	4	5

Project:	Submitted:
Customer:	Approved:
Location:	- T-F