



### STANDARD FEATURES

- Attractive spun aluminum exterior
- Belt drives permit easy performance adjustments when needed
- Curved non-overloading backward inclined wheel for efficiency at higher static pressures
- AMCA Air and Sound Licensed
- cULus 705 Listed



Size	A	B	C	D	Roof Opening	Curb O.D.	Damper (O.D.)	Average Ship Wt. Lbs.
6	18	30 1/8	25	3 3/8	13 1/2	16 1/2	12	109
7	18	30 1/8	25	3 3/8	13 1/2	16 1/2	12	109
8	18	30 1/8	25	3 3/8	13 1/2	16 1/2	12	109
10	18	30 1/8	25	3 3/8	13 1/2	16 1/2	12	109
12	20	31 11/16	27 5/8	3 7/8	15 1/2	18 1/2	14	122
14	20	31 11/16	27 5/8	3 7/8	15 1/2	18 1/2	14	126
15	24	32 1/2	32 7/8	4	19 1/2	22 1/2	18	140
16	24	32 1/2	32 7/8	4	19 1/2	22 1/2	18	140
18	30	36 3/8	39 3/16	4 5/8	25 1/2	28 1/2	24	156
20	30	38 5/16	45	6 1/8	25 1/2	28 1/2	24	166
22	30	38 5/16	45	6 1/8	25 1/2	28 1/2	24	170
24	36	46 5/8	49 3/8	6	31 1/2	34 1/2	30	270
27	36	49 1/16	49 3/8	8 1/2	31 1/2	34 1/2	30	280
30	42	50 1/4	56	7 3/8	37 1/2	40 1/2	36	300

NOTE: All dimensions shown are in inches.

FAN SPECIFICATIONS									MOTOR SPECIFICATIONS				
Line	Qty.	Model No.	Tag	CFM	SP	Fan RPM	BHP	Sones	HP	Volts	Phase	Hertz	Encl
1													
2													
3													
4													
5													

ACCESSORY ITEMS					1	2	3	4	5	ACCESSORY ITEMS					1	2	3	4	5
<input type="checkbox"/>										<input type="checkbox"/>									
<input type="checkbox"/>										<input type="checkbox"/>									
<input type="checkbox"/>										<input type="checkbox"/>									
<input type="checkbox"/>										<input type="checkbox"/>									
<input type="checkbox"/>										<input type="checkbox"/>									