



STANDARD FEATURES

- Exhaust air up to 4,780 CFM in high static pressure applications up to 1-1/2" w.g.
- Attractive spun aluminum exterior
- Direct drive units have low sound levels and quiet operation
- Curved non-overloading backward inclined wheel for efficiency at higher static pressures
- Roof or sidewall mounting options
- AMCA Air and Sound Licensed
- cULus 705 Listed
- NFPA - suitable for National Fire Protection Association Installations

STXD_e FEATURES

- cULus 705 Listed

STXD_eRHUL FEATURES

- Galvanized steel base
- Electrical connection located on shroud side with weather proof junction box
- cULus 762



* Only for STXD_e and STXD_eRHUL

Size	A	B	C	D	Roof Opening	Curb O.D.	Damper O.D.	Average Ship Wt. Lbs.
6	18	25 5/16	28 5/8	20 5/16	13 1/2	16 1/2	12	90
7	18	25 5/16	28 5/8	20 5/16	13 1/2	16 1/2	12	89
8	18	25 5/16	28 5/8	20 5/16	13 1/2	16 1/2	12	98
10	18	25 5/16	28 5/8	20 5/16	13 1/2	16 1/2	12	114
12	20	26 15/16	31 5/16	21 15/16	15 1/2	18 1/2	14	118
14	20	26 15/16	31 5/16	21 15/16	15 1/2	18 1/2	14	117
15	24	27 5/8	36 1/2	22 5/8	19 1/2	22 1/2	18	135
16	24	27 5/8	36 1/2	22 5/8	19 1/2	22 1/2	18	136

NOTE: All dimensions shown are in inches.

FAN SPECIFICATIONS									MOTOR SPECIFICATIONS				
Line	Qty.	Model No.	Tag	CFM	SP	Fan RPM	BHP	Sones	HP	Volts	Phase	Hertz	Encl
1													
2													
3													

ACCESSORY ITEMS					ACCESSORY ITEMS						
	1	2	3	4	5		1	2	3	4	5
<input type="checkbox"/>						<input type="checkbox"/>					
<input type="checkbox"/>						<input type="checkbox"/>					
<input type="checkbox"/>						<input type="checkbox"/>					